


CP930

3U Fast Ethernet Switch



Fast

Versatile


Robust

- Five **Fast** Ethernet Ports with a data throughput of 1400 Mbps
- **Versatile** design for use in CompactPCI, VME, standard PC or customer specific solutions.
- **Robust** and suited for harsh environments

Product Overview

Designed for operation in industrial automation applications, the CP930 is a rugged 5 port fast ethernet switch that can be used also in an extended temperature range of -40 to +85 °C.

CP930 supports 10Mbit/s and 100Mbit/s Fast Ethernet with RJ45 connectors; each of the five ports with two status LED's.
CP930-FX offers four RJ45 connectors and one fiber optical port with a 1300 nm MT-RJ connector.
CP930-RJ supplies four RJ45 connectors on the front and one internal RJ45 connector.



General

Number of ports: 5x TX or 4xTX and 1xFX
 Transfer rate: 10 and 100 Mbit/s with auto-negotiation
 Uplink: MDI/MDIX on all ports (auto-crossover)
 Power: 5 Volt nominal (4.7 to 7 Volt DC)
 maximum 2.2 Watt (3.9 Watt for the FX variant)

Controller

Controller: Unmanaged
 SRAM on chip: 128 kByte for frame buffering
 MAC addresses: integrated look-up engine with 2K MAC adresses

CP930-FX

Optical connector: MT-RJ, multimode, 1300 nm
 Distance: 2000 m

Common

Front Panel Connector.: RJ45 for copper and MT-RJ 1300nm for fiber
 Front Panel LED's: Activity and Speed
 Power connectors: 4 pin Molex (like on HDD's, 5 Volt DC only)
 J1 of CompactPCI (5 Volt DC only)
 Dimensions: 100 mm x 160 mm (3U / 4HP)
 CP930-FD: standard 3.5 inch
 Temperature Ranges: 0 °C to + 70 °C (standard)
 -40 °C to +85 °C (extended)
 Operation Humidity Range: 0..90% (non-condensing)
 Weight: 155 g
 MTBF: 148,000 h

Product	Description	Order No.
CP930	5 port Fast Ethernet switch with 5x RJ45 to the front	26304
CP930-E2	5 port Fast Ethernet switch with 5x RJ45 to the front, -40 °C / +85 °C temperature range	26307
CP930-FX	5 port Fast Ethernet switch with 4x RJ45 and 1x MT-RJ (1300 nm) to the front.	26305
CP930-RJ	5 port Fast Ethernet switch with 4x RJ45 to the front and 1x RJ45 onboard	26057

Corporate Offices

US/ Canada
 6260 Sequence Drive
 San Diego, CA 92121-4371
 Tel.: +1 (0) 88 82 94 45 58
 Fax: +1 (0) 88 86 77 08 98
 sales@kontron.com

Europe, Middle East and Africa
 Oskar-von-Miller-Straße 1
 85386 Eching/Munich Germany
 Tel.: +49 (0) 8165 77 0
 Fax: +49 (0) 8165 77 219
 sales@kontron.com

Asia Pacific
 2F, No. 2, Lane 50, Nankang Rd., sec 3
 Nankang district, Taipei Taiwan
 Tel.: +886 2 2782 0201
 Fax: +886 2 2782 7486
 sales@kontron.com.tw

Kontron Modular Computers GmbH
 Sudetenstr. 7
 D-87600 Kaufbeuren
 Tel.: +49 (0) 8341 803 0
 Fax: +49 (0) 8341 803 499
 www.Kontron.com

Our worldwide sales representatives and partners can be found on our websites.